

Tarviso


5841A2EJ4



SIOPOR[®]
EXTRA

Signalisatie regenbroek

100% waterdicht / Winddicht / Hoogademend / Waterafstotende buitenstof / Vochtabsorberende coating aan binnenkant / Comfortabel / Soepel / Hoge scheurbestendigheid



Signalisatie regenbroek

Tarviso - 5841A2EJ4

Europese normeringen:

- » EN ISO 20471 : 2013 / Class 1
- » EN 343 : 2003 + A1 : 2007 / Class 3-3
- » CE
- » EN ISO 13688 : 2013
- » Tested for harmful substances according to Oeko-Tex® Standard 100 (1011041/Centexbel) / Fabric

Buitenkant:

- » Gulp met drukknopen
- » 2 ingezette zakken
- » Vernauwing aan beenuiteinde d.m.v. drukknopen
- » Elastiek in lenden met koord
- » Naden waterdicht getapet

Binnenkant:

- » Vaste polyamide voering

Stof:

SIOPOR® Extra: 100% polyester weefsel (cotton touch) met 100% PU laminaat; ± 205 g/m²

Maten:

XS - XXXL

Kleur:

- » 414 Fluo Oranje/Marine
- » 415 Fluo Geel/Marine
- » 952 Fluo Geel/Grijs

In combinatie met:

132Z (p.169) - 403Z (p.169) - 497Z (p.106) - 703Z (p.172) - 708Z (p.170) - 711Z (p.111) - 712Z (p.110) - 722Z (p.113) - 724Z (p.113) - 725Z (p.109) - 9852 (p.104) - 9933 (p.115)

Verpakking:

- » 10 stuks per doos

Was- & onderhoudsinstructies:



SIOEN head office

Fabriekstraat 23

B-8850 Ardoorie

Belgium

T: +32 (51) 740 800

F: +32 (51) 740 962

www.sioen-ppc.com



Discover
our products

© 2016 SIOEN - Protection through Innovation, Flexothane®, Siopor® and the SIOEN logo are trademarks of the SIOEN Industries Group.

Please note that all information given in this document is intended to be useful and informative and is correct to the best of our knowledge at time of print. No liability can be accepted for inaccuracies or omissions. The right is reserved to amend this information without prior notice.

All our technical files, style descriptions, presentations, designs and drawings, give the latest update of the standards and design or style features of each product. However, delivered products may comply with previous standards, design or style features. For that SIOEN disclaims any liability whatsoever. Contact our sales for full information if specific requirements are needed.